



5.5 mil PhotoRealistic Paper

Low Glare



Non Resin-coated photorealistic paper is an economical choice for full ink coverage while keeping cost per sq. foot down.

Opacity	97
Gloss (60 degrees)	42
Whiteness	>100
Brightness	96
Caliper	5.5 mil
Basis Weight	170g/m2

Specifications

Ink coverage up to 300%

For optimum results, use the following printer settings:

- HP 2000/3000 - "semi-gloss photo"
- HP 5000 - "Photo Imaging Gloss"
- Encad NovaJet - "enhanced Multi-Pass"

Inks: Dye-Based only

Printers:

- ColorSpan
- Encad NovaJet Pro
- Kodak 4000 series
- Hewlett-Packard DesignJet
 - 650
 - 750
 - 1000 Series
 - 2000 Series
 - 3000 Series
 - 5000 Series

Printer & Ink Compatibility

LAMINATION

Can be overlaminated with most cold and low-temp hot laminates. Better adhesion is achieved using cold laminate. Overlap the image with minimum .25 inch safe edge to prevent moisture absorption and premature paper splitting. Lamination can be performed immediately after printing as long as the inks are dry to the touch and do not smear.

MOUNTING

Recommended mounting material is cold, pressure-sensitive adhesive to provide the best bond.

Lamination & Mounting